



PCB terminal block — TLM series ( Screwless Type ) — TLM-212V



■ 图示(Pic. shown) : TLM-212V-06P-G12

General.	PCB terminal block	Rated : 320V,24A	2.5mm <sup>2</sup>
	Single row , 5.00mm pitch , 02-24 Pole		
	Wiring orientation:90°(wire-to-board)		
	Screwless Type		

认证 ( Approval )

技术参数 Technical Data	UL standard			IEC standard		
	UL Application group			IEC过电压别/污染等级(IEC overvoltage category /pollution degree)		
UL应用组别(UL Application group)	B	C	D	III / 3	III / 2	II / 2
IEC过电压别/污染等级(IEC overvoltage category /pollution degree)				250V	320V	630V
额定电压(Rated voltage)	300V	--	300V	24A	24A	24A
额定电流(Rated current)	20A	--	10A	0.2-2.5mm <sup>2</sup> Sol&Str / 4.0mm <sup>2</sup> Sol		
额定连接容量(Rated connection capacity)	26-12 AWG Sol&Str			PA66 UL94 V-0		
绝缘材料(Insulation Material)				Copper alloy , Tin plated		
电流承载部件材料和镀层( Material & Plating of Current carrier )				Stainless Steel		
接线弹片材料(Material of Clamp spring )				500MΩ or more at DC500V		
绝缘电阻(Insulation Resistance)				2500V		
耐电压(1分钟)(Withstanding Voltage/1Min)				4000V		
额定冲击电压(Rated surge voltage)				--		
接线螺丝(Wire clamp unit Screw) , 最大扭矩( torque Max. )				--		
固定螺丝(Mounting Screw) , 扭矩(torque)				10mm		
剥线长度(Wire stripping length)				-40°C up to +115°C		
使用温度(Operating temperature)				Wave soldering ,260°C 5S Max (Single Wave) , 260°C 10S Max(Double Wave)		
焊接方式(Soldering recommend)						

■ 订购方式(How to order)

